



TEXTREME® 1051 – HS SPREAD TOW CARBON FIBER 12K 39.37"/100CM 1.89OZ/64GSM MODEL #: F-1112-39

Warp tape:	UTS50 12K F22 S	32 gsm
Weft tape:	UTS50 12K F22 S	32 gsm
Stabilizing material:	NM688	10 gsm
Total fiber weight:		64 gsm
Weave pattern:		Plain Weave
Sizing:		Epoxy compatible
Width of tape 0°/90°:		25 / 25 mm
Width of fabric:		1000 mm
Thickness of one ply laminate @ 60% Vf:		0.064 mm



STORAGE

The fabric and tape should be stored in a dry and well ventilated place at room temperature (0 - 30°C) unless otherwise specified. The fabric roll should be stored without any load i.e. the roll must be kept in a stand or stored in the appropriate box so that the paper core takes all the load. TeXtreme has a guaranteed shelf life of two (2) years from the date of production under the condition that the product has been transported, processed and stored according to the stated requirements.

Information and data included in this data sheet is considered to be accurate and reliable to the best of our knowledge however it is not guaranteed to be so. It is the user/buyer's responsibility to determine for themselves the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. Composite Envisions make no representations or warranties as to the results to be obtained in using any material. As Composite Envisions cannot foresee all conditions under which products will be used, user/buyer waives any claim against Composite Envisions for direct, indirect, consequential, or exemplary damages including without limitation, damage which may incur as a result of user/buyer's use or misuse of the product or the product's failure to perform to any expected performance level.

Composite Envisions LLC
8450 Development Court
Wausau, WI 54401 USA
+1 715-842-0101
info@compositeenvisions.com
<https://compositeenvisions.com/>



COMPOSITE ENVISIONS