



## TEXTREME® 1005 - HM HIGH MODULUS SPREAD TOW CARBON FIBER HS40 MODEL #: F-1116-39

### SPREAD TOW FABRIC SPECIFICATION

**Warp tape:** HS40 12K DD - 65 gsm

**Weft tape:** HS40 12K DD - 65 gsm

**Stabalizing material:** NM688 - 15 gsm

**Total fiber weight:** 130 gsm

**Weave pattern:** Plain Weave

**Sizing:** Epoxy compatible

**Width of tape 0° / 90°:** 20 / 20mm

**Width of fabric:** 1000mm

**Thickness of one ply laminate @ 60% Vf:** 0.130mm



Information and data included in this data sheet is considered to be accurate and reliable to the best of our knowledge however it is not guaranteed to be so. It is the user/buyer's responsibility to determine for themselves the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. Composite Envisions make no representations or warranties as to the results to be obtained in using any material. As Composite Envisions cannot foresee all conditions under which products will be used, user/buyer waives any claim against Composite Envisions for direct, indirect, consequential, or exemplary damages including without limitation, damage which may incur as a result of user/buyer's use or misuse of the product or the product's failure to perform to any expected performance level.

Composite Envisions LLC  
8450 Development Court  
Wausau, WI 54401 USA  
+1 715-842-0101  
[info@compositeenvisions.com](mailto:info@compositeenvisions.com)  
<https://compositeenvisions.com/>



# COMPOSITE ENVISIONS