A&P Technology

4595 East Tech Drive Cincinnati, OH 45245-1055

TEL: 513-688-3200 sales@braider.com

FAX: 513-672-9996 www.braider.com

QISO-H-48

Raw Material: BIAS: T-700 SC 12K 50C (Toray)

AXIAL: T-700 SC 12K 50C

Fabric Width: 47.9"

Braid Angle: $0, +/-60^{\circ}$

Braid Yield: 0.76 yd/lb

Areal Weight: 536 GSM

Layer Thickness: 0.021 in (55% Fiber Volume)

QISO® Triaxial Carbon Fabric

QISO® fabric is available in different standard areal weights, and can be customized to meet raw material or specific weight requirements.

For more information please visit www.braider.com, or contact a sales representative at 513-688-3200

SAFETY DATA SHEET

Carbon Fiber "TORAYCA" Sizing Type "5"

1. IDENTIFICATION

COMPANY: Toray Carbon Fibers America, Inc.

SECTION: Technical Center

ADDRESS: 2030 Highway 20; Decatur, AL 35602 USA

TEL No.: (256) 260-2626; contact: Director of Technical Center

FAX No.: (256) 260-1063

2. HAZARDS IDENTIFICATION (Environmental, Safety and Health)

2.1 CLASS NAME OF HAZARDOUS CHEMICALS FOR SDS

Non-hazardous material

2.2 PHYSICAL & CHEMICAL HAZARDS

Explosive: N/A

2.3 ADVERSE HUMAN HEALTH EFFECTS

Acute Toxic Substance: No case of disease, which is caused by Carbon Fiber, has been reported. Short fiber, for example particles or fly, can cause transient skin irritation.

2.4 ENVIRONMENTAL EFFECTS

- 2.4.1 Carbon Fiber is electrically conductive, and it can cause the short-circuiting of electrical equipment.
- 2.4.2 Airborne Carbon Fiber can also disturb electrical equipment.

2.5 HEALTH HAZARD DATA

Primary Route of Entry: Inhalation, Eyes, Dermal, Ingestion

Effects of Overexposure:

Inhalation: Nuisance dust may cause temporary but reversible respiratory

problems.

Eyes: Abrasive action may cause damage to the outer surface of the eye.

Avoid wearing contact lenses if airborne carbon fiber/particle fly is

particularly heavy.

Skin Contact: Fiber contact may cause slight itching and irritation.

Ingestion: Not a likely source of entry due to physical nature of material.

Chronic: Product does not contain carcinogenic materials as defined by

OSHA Communication Act 1910.1200.

3. COMPOSITION INFORMATION ON INGREDIENTS

CHEMICAL TYPE: Carbon (Carbon Fiber)

CAS Number: 7440-44-0

SUBSTANCE () MIXTURE (O): UN CLASS & UN NUMBER: N. A.

Chemical Name	Comp.	Chemical Formula	CAS No.	TSCA
	(%)	(Constitutional Formula, Structural		
		Formula)		
Carbon Fiber	<u>≥</u> 94	Carbon Fiber	7440-44-0	Registered
Sizing Agent	<u><</u> 2	Not open to public	Registered	Registered

4. FIRST-AID MEASURES

4.1 INHALATION

Move to fresh air and wash inside of mouth with water. If dizzy or unbalanced, seek medical attention as soon as possible.

4.2 SKIN CONTACT

If transient skin irritation occurs, remove contaminated clothing and wash thoroughly with soap and water. If irritation persists, seek medical attention. Wash contaminated clothing before reuse.

4.3 EYE CONTACT

Immediately wash eyes with an excessive amount of water for at least 15 minutes. If contacts are being used, remove the lens and flush the eyes again with water for an additional 5 to 10 minutes. If the eyes feel uncomfortable or have prickly feeling, seek medical attention as soon as possible.

4.4 INGESTION

Do not induce vomiting. Rinse mouth with fresh water. Then drink two or three glasses of water. Seek medical attention as soon as possible.

5. FIRE-FIGHTING MEASURES

5.1 SPECIFIC HAZARDS WITH REGARD TO FIRE-FIGHTING MEASURES

Apply water from a safe distance to cool and protect surrounding area.

5.2 EXTINGUISHING MEDIA

In case of fire, use water spray, foam, dry chemical powder or carbon dioxide.

Dry chemical powder, carbon dioxide or dry sand should be used for small fires.

CFA 005 SDS-3 2 Page **2** of **6**

6. ACCIDENTAL RELEASE MEASURES

6.1 MEASURES FOR HANDLING PERSONNEL

No special measures requested

6.2 MEASURES FOR ENVIRONMENTAL EFFECTS

No special measures requested

6.3 MEASURES WHEN HANDLING SPILLED SUBSTANCE

N/A

7. HANDLING AND STORAGE

7.1 HANDLING

Exposure control for individuals handling product:

Contact with carbon fiber can cause transient skin irritation. Hold the paper tube when handling bobbins to limit contact. To limit exposure wear cloth/leather gloves and cover exposed areas with normal work clothing. Additional protection may be needed if particle limits are excessive.

Protective measures against fire & explosion: N/A

7.2 STORAGE

Store bobbins in a cool, dark space. Low humidity is recommended.

..., ...

8. EXPOSURE CONTROL / PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

No data are available for the product

Content	Carbon Fiber	
LABOR SAFETY & HEALTH ACT(JAPAN)	2.9mg/m ³ (reference value by "Kokuji"	
ppm (mg/m³)	by Min. of Labor Japan (1995))	
OSHA	2.0mg/m ³ as the total dust of first class	
ppm (mg/m³)	dust by the Japanese regulation	
	(reference value) etc.	
ACGIH	10.0mg/m³ as the "kyuunyuusei" dust not	
ppm (mg/m³)	classified to other categories, etc.	
	(reference value)	

8.2 ENGINEERING MEASURES

Local extract ventilation is recommended where dust and fly are generated by cutting or processing Carbon Fiber. Filter in ventilation is requested to prevent dust and fly from being discharged into open air.

CFA 005 SDS-3 3 Page **3** of **6**

8.3 PERSONAL PROTECTIVE EQUIPMENT

- 8.3.1 Respiratory protection: Adequate respirator is suggested to keep from inhaling dust and fly particles.
- 8.3.2 Eye protection: Adequate protective goggles are suggested to keep eyes from dust and fly.
- 8.3.3 Hand, skin and body protection: Adequate protective gloves are suggested to keep skin from dust and fly.

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance : Black fiber	Odor : None
Density: 1.6~2.0	Boiling point : N/A
Melting point : N/A	Vapor pressure : N/A
Vapor density : N/A	Solubility(%): In soluble in water: N/A in others: N/A
Volatility : N/A	Others: N/A

10. STABILITY & REACTIVITY (PHYSICAL HAZARD)

Flash point : None	Spontaneous ignition temperature : None	
Explosion limit (%): None	Combustibility: Not Spontaneous	
Upper: None	Reactivity with water: None	
Lower: None		
Flammability: N/A	Dust explosion: N/A	
Oxidizibility:	Self-reactivity: None	
Oxidized by strong oxidizer.		
Stable for other chemicals		

Oxidation can progress slowly and become red-hot when exposed to high temperatures greater than 240°C in air.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: N/A

Sub-chronic toxicity: N/A

CFA 005 SDS-3 4 Page **4** of **6**

4 of 6

Chronic toxicity: N/A

Carcinogenic effects: No silicosis case has been reported on inhalation test with mouse.

Mutagenic effects: In one component of Sizing Agent, Bisphenol A epoxy resin, the mutagenic

effect on a microbe is recognized.

Irritant properties: Contact with fly or dust can cause skin irritation.

Teratogenic effects: N/A

12. ECOLOGICAL INFORMATION

Biodegradability: N/A Bioaccumulation: N/A Fish toxicity: N/A

13. DISPOSAL CONSIDERATION

13.1 In case of disposal, this product must be treated as industrial waste, separated from public waste.

13.2 This product should not be incinerated. Carbon fiber can not be incinerated well by a general incinerator, and the fibrous fragments, which may be generated by insufficient incineration, may cause the short-circuiting of electrical equipment.

14. TRANSPORTATION INFORMATION

N/A

15. REGULATORY INFORMATION

Regulatory/Classification	Reg. Info.	Substance Name	Allowed Concentration	
TSCA (USA) No.	N/A	7440-44-0	N/A	N/A
		Carbon Fiber		
EINECS No.	N/A	N/A	N/A	N/A
California Proposition 65	N/A	N/A	N/A	N/A
FDA	N/A	N/A	N/A	N/A
UL	N/A	N/A	N/A	N/A
CAS	N/A	7440-44-0	N/A	N/A
REACH	Article Only	Carbon Fiber	N/A	N/A
OSHA	N/A	N/A	N/A	N/A

16. OTHER INFORMATION INCLUDING DATE OF PREPARATION OF LAST REVISION:

SDS NUMBER.: CFA-005 SDS-3

Document History:

Date: Dec. 3, 1999 Rev: December 2, 2008 Reviewed: January 31, 2012 Revised June 29, 2015

Although the information and recommendations set forth herein (hereinafter 'Information') are presented in good faith and believed to be correct as of the date hereof, Toray Carbon Fibers America Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will Toray Carbon Fibers America Inc. be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCANTABIBLTY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.