



SAFETY DATA SHEET

LUPEROX® DDM-9 RED

1. PRODUCT AND COMPANY IDENTIFICATION**Company**

Arkema Inc.
900 First Avenue
King of Prussia, Pennsylvania 19406

Functional Additives

Customer Service Telephone Number: (800) 331-7654
(Monday through Friday, 8:00 AM to 5:00 PM EST)

Emergency Information

Transportation: CHEMTREC: (800) 424-9300
(24 hrs., 7 days a week)
Medical: Rocky Mountain Poison Center: (866) 767-5089
(24 hrs., 7 days a week)

Product Information

Product name: LUPEROX® DDM-9 RED
Synonyms: Not available
Molecular formula: Complex mixture
Chemical family: Organic peroxide - ketone peroxides
Product use: initiator/catalyst

2. HAZARDS IDENTIFICATION**Emergency Overview**

Color: red
Physical state: liquid
Form: oily
Odor: sweet

***Classification of the substance or mixture:**

Flammable liquid., Category 4, H227
Organic peroxides, Type D, H242
Skin corrosion, Category 1B, H314
Serious eye damage, Category 1, H318
Chronic aquatic toxicity, Category 3, H412

*For the full text of the H-Statements mentioned in this Section, see Section 16.

LUPEROX® DDM-9 RED

GHS-Labeling

Hazard pictograms:



Signal word:

Danger

Hazard statements:

H227 : Combustible liquid.

H242 : Heating may cause a fire.

H314 : Causes severe skin burns and eye damage.

H412 : Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements:

Organic peroxide.

Hazardous decomposition may occur.

LUPEROX® DDM-9 RED
Precautionary statements:
Prevention:

P210 : Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P220 : Keep/Store away from clothing/ combustible materials.
P234 : Keep only in original container.
P264 : Wash skin thoroughly after handling.
P273 : Avoid release to the environment.
P280 : Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P330 + P331 : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 : IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 : Immediately call a POISON CENTER/doctor.
P363 : Wash contaminated clothing before reuse.
P370 + P378 : In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P405 : Store locked up.
P410 : Protect from sunlight.
P411 + P235 : Maximum storage temperature is specified on label and in section 7 of SDS. Keep cool.
P420 : Store away from other materials.

Disposal:

P501 : Dispose of contents/ container to an approved waste disposal plant.

Supplemental information:
Potential Health Effects:

If swallowed, may cause severe irritation and injury to the mouth, throat and digestive tract.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Wt/Wt	GHS Classification**
Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester	6846-50-0	>= 57 - <= 59 %	H412

LUPEROX® DDM-9 RED

2-Butanone, peroxide	1338-23-4	$\geq 32 - \leq 34 \%$	H242, H302, H314, H318
2,4-Pentanediol, 2-methyl-	107-41-5	$\geq 5.5 - \leq 6.5 \%$	H319, H336
2-Butanone	78-93-3	$\geq 1 - \leq 2 \%$	H225, H319, H336

**For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES
4.1. Description of necessary first-aid measures:
Inhalation:

If inhaled, remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Skin:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyes:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Ingestion:

If swallowed, DO NOT induce vomiting. Get medical attention immediately. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms/effects, acute and delayed:

For most important symptoms and effects (acute and delayed), see Section 2 (Hazard Statements and Supplemental Information) and Section 11 (Toxicology Information) of this SDS.

4.3. Indication of immediate medical attention and special treatment needed, if necessary:

Unless otherwise noted in Notes to Physician, no specific treatment noted; treat symptomatically.

5. FIREFIGHTING MEASURES
Extinguishing media (suitable):

LUPEROX® DDM-9 RED

Water spray, Foam, Dry chemical, Carbon dioxide (CO₂)

Extinguishing media (unsuitable):

Water may be ineffective., Do not use a solid water stream as it may scatter and spread fire.

Protective equipment:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

Further firefighting advice:

Fight fire with large amounts of water from a safe distance.

Cool closed containers exposed to fire with water spray.

Closed containers of this material may explode when subjected to heat from surrounding fire.

After a fire, wait until the material has cooled to room temperature before initiating clean-up activities.

Do not allow run-off from fire fighting to enter drains or water courses.

Fire fighting equipment should be thoroughly decontaminated after use.

Fire and explosion hazards:

Contact with incompatible materials or exposure to temperatures exceeding the SADT may result in a self accelerating decomposition reaction with release of flammable vapors which may autoignite.

When burned, the following hazardous products of combustion can occur:

Carbon oxides

Hazardous organic compounds

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, Emergency procedures, Methods and materials for containment/clean-up:**

Prevent further leakage or spillage if you can do so without risk. Evacuate area of all unnecessary personnel.

Ventilate the area. Eliminate all ignition sources. Avoid generation of vapors. Contain and collect spillage with non-combustible absorbent material such as sodium bicarbonate, sodium carbonate, calcium carbonate, clean sand or non-acidic clay and then wet down (dampen) the mixture with water. DO NOT USE peat moss. DO NOT USE vermiculite. Sweep or scoop up using non-sparking tools and place into suitable properly labeled containers for prompt disposal. The sweepings should be wetted down further with water. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

Protective equipment:

Appropriate personal protective equipment is set forth in Section 8.

LUPEROX® DDM-9 RED**7. HANDLING AND STORAGE****Handling****General information on handling:**

Contact with materials to avoid or exposure to temperatures exceeding the SADT may result in a self-accelerating decomposition reaction with release of flammable vapors which may autoignite.

Do not taste or swallow.

Do not get in eyes, on skin, or on clothing.

Avoid breathing vapor or mist.

Keep away from heat, sparks and flames.

No smoking.

Use only with adequate ventilation.

Wash thoroughly after handling.

Prevent product contamination.

Keep container tightly closed and away from combustible materials.

Keep only in the original container.

Check that all equipment is properly grounded and installed to satisfy electrical classification requirements.

Container hazardous when empty.

Follow label warnings even after container is emptied.

RESIDUAL VAPORS MAY EXPLODE ON IGNITION.

DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR THIS CONTAINER.

Emptied container retains product residue.

Do not reuse container as it may retain hazardous product residue.

Observe all labeled safeguards until container is cleaned, reconditioned or destroyed.

Improper disposal or reuse of this container may be dangerous and/or illegal.

Storage**General information on storage conditions:**

Keep container closed when not in use. Store in closed containers, in a secure area to prevent container damage and subsequent spillage. Outside or detached storage is preferred. Store in well ventilated area away from heat and sources of ignition such as flame, sparks and static electricity. Ensure that all storage and handling equipment is properly grounded and installed to satisfy electrical classification requirements. Store out of direct sunlight in a cool well-ventilated place. Store in upright position only. Store in original container. Store away from combustibles and materials to avoid. Refer also to National Fire Protection Association (NFPA) Code 400, Hazardous Materials Code. Static electricity may accumulate when transferring material. All metal and groundable storage containers, including but not limited to drums, cylinders, Returnable Intermodal Bulk Containers (RIBCs) and Class C Flexible Intermodal Bulk Containers (FIBCs) must be bonded and grounded during filling and emptying operations. Observe all federal, state and local regulations and National Fire Protection Association (NFPA) Codes which pertain to the specific local conditions of storage and use, including OSHA 29 CFR 1910.106 and NFPA 30, 70, 77, and 497.

Storage stability – Remarks:

Follow the recommended storage temperatures provided in this Section in order to maintain stability and oxygen content.

Storage incompatibility – General:

Store away from excessive heat, sources of ignition, and reactive materials.

Store separate from:

Strong acids

Strong bases

Strong oxidizing agents

Reducing agents

LUPEROX® DDM-9 RED

Accelerators
Friedel - Crafts reaction catalyst
transition metal salts
metal ions
Brass
Copper
Iron

For all Organic Peroxides, compatible materials of contact are stainless steel 304 or 316 (preferred), high-density polyethylene (HDPE), polytetrafluoroethylene or glass linings.

Temperature tolerance – Do not store below:
50 °F (10 °C)

Temperature tolerance – Do not store above:
100 °F (38 °C)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne Exposure Guidelines:

2-Butanone, peroxide (1338-23-4)

US. ACGIH Threshold Limit Values

Ceiling Limit Value	0.2 ppm
---------------------	---------

2,4-Pentanediol, 2-methyl- (107-41-5)

US. ACGIH Threshold Limit Values

Ceiling Limit Value	25 ppm
---------------------	--------

2-Butanone (78-93-3)

US. ACGIH Threshold Limit Values

Time weighted average	200 ppm
Short Term Exposure Limit (STEL):	300 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

PEL:	200 ppm (590 mg/m ³)
------	----------------------------------

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

LUPEROX® DDM-9 RED

Engineering controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Consult ACGIH ventilation manual or NFPA Standard 91 for design of exhaust systems.

Respiratory protection:

Avoid breathing vapor or mist. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components. Full facepiece equipment is recommended and, if used, replaces need for face shield and/or chemical goggles. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Skin protection:

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Wear chemical goggles, a face shield, and chemical resistant clothing such as a rubber apron when splashing may occur. Rinse immediately if skin is contaminated. Remove contaminated clothing immediately and wash before reuse. Clean protective equipment before reuse. Provide a safety shower at any location where skin contact can occur. Wash thoroughly after handling.

Eye protection:

Where there is potential for eye contact, wear a face shield, chemical goggles, and have eye flushing equipment immediately available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	red
Physical state:	liquid
Form:	oily
Odor:	sweet
Odor threshold:	No data available
Flash point	180 °F (82 °C) (Setaflash closed cup)
Auto-ignition temperature:	No data available.
Lower flammable limit (LFL):	No data available
Upper flammable limit (UFL):	No data available

LUPEROX® DDM-9 RED

pH:	No data available
Density:	1.0070 g/cm ³ (68 °F (20 °C))
Specific Gravity (Relative density):	1.0088 (68 °F (20 °C))Water=1 (liquid)
Vapor pressure:	5.20 mmHg (66 °F (19 °C))
Boiling point/boiling range:	Decomposes before boiling. Rate of decomposition increases with rising temperature.
Melting point/range:	No data available.
Freezing point:	No data available
Evaporation rate:	No data available
Solubility in water:	slightly soluble
Refractive index:	1.4356
Viscosity, dynamic:	17.30 mPa.s 68 °F (20 °C)
Oil/water partition coefficient:	No data available.
Self-Accelerating Decomposition Temperature (SADT):	estimated 167 °F (75 °C) 45 pound container
Thermal decomposition:	Decomposes on heating.
Active oxygen content:	8.7 - 9.0 %
Flammability:	See GHS Classification in Section 2

10. STABILITY AND REACTIVITY

Stability:

This material is chemically unstable and should only be handled under specified conditions. See HANDLING AND STORAGE section of this MSDS for specified conditions.

Hazardous reactions:

Hazardous polymerization does not occur.

Materials to avoid:

Strong acids
Strong bases
Strong oxidizing agents
Reducing agents
Accelerators

LUPEROX® DDM-9 RED

Friedel - Crafts reaction catalyst
transition metal salts
metal ions
Brass
Copper
Iron

For all Organic Peroxides, compatible materials of contact are stainless steel 304 or 316 (preferred), high-density polyethylene (HDPE), polytetrafluoroethylene or glass linings.

Conditions / hazards to avoid:

See HANDLING AND STORAGE section of this MSDS for specified conditions. SADT - Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction. This reaction will generate flammable vapors which may autoignite. The length of time to generate a decomposition reaction, after the SADT has been reached or exceeded, is dependent upon how much the SADT has been exceeded and the length of time needed for the reaction exotherm (heat spike from increasing decomposition rate) to initiate a rapid decomposition reaction. Typically, SADT is inversely proportional to package size. Larger packages will have a lower SADT due to smaller ratio to heat transfer area to volume of product.

Hazardous decomposition products:

Temperatures at or above SADT can result in the release of hazardous decomposition products which are flammable and may autoignite.

Thermal decomposition giving flammable and toxic products :

Carbon oxides

Hazardous organic compounds

11. TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

Data for LUPEROX® DDM-9 RED**Acute toxicity****Oral:**

Acute toxicity estimate 2,867 mg/kg.

Dermal:

Acute toxicity estimate > 5,000 mg/kg.

Inhalation:

4 h Acute toxicity estimate > 40 mg/l. (vapor)

Data for Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester (6846-50-0)**Acute toxicity****Oral:**

No deaths occurred. (rat) LD₀ > 2,000 mg/kg.

Dermal:

No deaths occurred. (rabbit) LD₀ > 2,000 mg/kg.

LUPEROX® DDM-9 RED

Inhalation:

No deaths occurred. (rat) 6 h LC0 > 5.3 mg/l.

Skin Irritation:

Not irritating. (rabbit) Irritation Index: 0/8. (4 h)

Eye Irritation:

Causes mild eye irritation. (rabbit)

Skin Sensitization:

Not a sensitizer. Repeated skin exposure. (guinea pig) No skin allergy or irritation was observed.

Repeated dose toxicity

Repeated oral administration to rat / affected organ(s): kidney, liver / signs: clinical chemistry changes, changes in organ weights, hyaline droplet nephropathy / (not considered relevant in humans)

Subchronic dietary administration to dog / No adverse systemic effects reported.

Genotoxicity

Assessment in Vitro:

No genetic changes were observed in laboratory tests using: bacteria, animal cells

Developmental toxicity

Reproductive/Developmental Effects Screening Assay. dietary (rat) / No birth defects were observed.

Reproductive effects

Reproductive/Developmental Effects Screening Assay. dietary (rat) / No toxicity to reproduction. At high dose : levels produced toxic effects in the mothers and offspring

Human experience

Skin contact:

No skin allergy was observed. (studied using human volunteers)

Data for 2-Butanone, peroxide (1338-23-4)

Acute toxicity

Oral:

Harmful if swallowed. (rat) LD50 = 1,017 mg/kg. (35 - 39 %) (In solution in Dimethyl phthalate)

Dermal:

Harmful in contact with skin. (rabbit) LD50 = 4,000 mg/kg. (35 - 39 %) (In solution in Dimethyl phthalate)

Inhalation:

Practically nontoxic. (rat) 4 h LC50 = 17 mg/l. (35 - 39 %) (aerosol, In solution in Dimethyl phthalate)

Skin Irritation:

Causes severe skin burns. (rabbit) (4 h) (33 %) (occluded exposure, In solution in Dimethyl phthalate)

Eye Irritation:

Causes serious eye damage. (rabbit) OECD Test Guideline 405 (33 - 39 %) (In solution in Dimethyl phthalate)

LUPEROX® DDM-9 RED**Skin Sensitization:**

Not a sensitizer. Guinea pig maximization test. No skin allergy was observed (40 %) (In solution in Dimethyl phthalate)

Repeated dose toxicity

Repeated oral administration to rat / affected organ(s): Stomach, liver / signs: Irritation of the gastric mucosa, increased organ weight

Subchronic dermal administration to rat and mouse / affected organ(s): skin / signs: severe damage / No adverse systemic effects reported.

Genotoxicity**Assessment in Vitro:**

Both positive and negative responses for genetic changes were observed in laboratory tests using: bacteria, animal cells

Genotoxicity**Assessment in Vivo:**

No genetic changes were observed in laboratory tests using: mice

Developmental toxicity

Reproductive/Developmental Effects Screening Assay. Oral (rat) / No birth defects were observed.

Reproductive effects

Reproductive/Developmental Effects Screening Assay. Oral (rat) / No toxicity to reproduction.

Human experience**Skin contact:**

No skin allergy was observed. (studied using human volunteers)

Skin allergy was observed. Isolated case reports after exposure to a mixture containing this substance.

Human experience**Eye contact:**

Eyes: Pain, tearing, sensitivity to light, irritation. Mist and/or vapor are reported to cause irritation when proper industrial hygiene controls/procedures are not used. (based on reports of occupational exposure to workers) (severity of effects depends on extent of exposure)

Eyes: Pain, causes severe burns. (accidental exposure to concentrated solutions) (based on reports of occupational exposure to workers) (severity of effects depends on extent of exposure)

Human experience**Ingestion:**

Esophagus: Severe irritation, burns. (accidental exposure to concentrated solutions)

Data for 2,4-Pentanediol, 2-methyl- (107-41-5)**Acute toxicity****Oral:**

No deaths occurred. (rat) LD₀ > 2,000 mg/kg. signs: GI tract irritation, central nervous system

LUPEROX® DDM-9 RED

depression

Dermal:

No deaths occurred. (rat) LD₀ > 2,000 mg/kg.

Inhalation:

No deaths occurred. (rat) 8 h LC₀ >= 0.34 mg/l (70 ppm). (saturated vapor)

Specific target organ toxicity - single exposure:

May cause drowsiness or dizziness.

Skin Irritation:

Practically non-irritating. (rabbit) (4 h)

Eye Irritation:

Causes serious eye irritation. (rabbit)

Skin Sensitization:

Not a sensitizer. Guinea pig maximization test. No skin allergy was observed

Repeated dose toxicity

Subchronic oral administration to rat / affected organ(s): kidney, liver, Stomach / signs: Irritation of the gastric mucosa / No significant impairment of function.

Repeated inhalation administration to rat / affected organ(s): upper respiratory tract / Local irritation (Aerosol)

Genotoxicity**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells

Developmental toxicity

Exposure during pregnancy. Oral (rat) / No birth defects were observed. (delays in development, at doses that produce effects in mothers)

Reproductive effects

Reproductive/Developmental Effects Screening Assay. Oral (rat) / No toxicity to reproduction. At high dose : Effects on offspring / (increased mortality in the offspring, decreased growth rate)

Human experience**Inhalation:**

Discomfort. (severity of effects depends on extent of exposure) (studied using human volunteers)

Human experience**Skin contact:**

No skin allergy was observed. (studied using human volunteers)

Local irritation, redness, swelling. (subjects with dermatitis or eczema)

Central nervous system depression. (severity of effects depends on extent of exposure)

Human experience

LUPEROX® DDM-9 RED**Eye contact:**

Discomfort, slightly irritating. (liquid or aerosol) (studied using human volunteers) (severity of effects depends on extent of exposure)

Data for 2-Butanone (78-93-3)**Acute toxicity****Oral:**

May be harmful if swallowed. (rat) LD50 = 2,600 - 5,400 mg/kg.

Dermal:

Practically nontoxic. (rabbit) LD50 > 6,400 - 8,000 mg/kg.

Inhalation:

Practically nontoxic. (rat) 4 h LC50 = 34.5 mg/l (11700 ppm).

Specific target organ toxicity - single exposure:

May cause drowsiness or dizziness.

Skin Irritation:

Causes mild skin irritation. (rabbit) (24 h)

Eye Irritation:

Causes serious eye irritation. (rabbit) Draize Test 21/110.

Skin Sensitization:

Not a sensitizer. Buehler method. (guinea pig) No skin allergy was observed

Repeated dose toxicity

Subchronic inhalation administration to rat / affected organ(s): liver / signs: blood chemistry changes, changes in organ weights

Repeated inhalation administration to rat, mouse, cat, chicken / no nervous system injuries

Carcinogenicity

Chronic dermal application administration to mouse / No increase in tumor incidence was reported.

Genotoxicity**Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells, human cells

Both positive and equivocal responses have been reported in tests using: yeast

Genotoxicity**Assessment in Vivo:**

No genetic changes were observed in laboratory tests using: mice, hamster

Developmental toxicity

Exposure during pregnancy. inhalation (mouse) / No birth defects were observed. (skeletal variations, delays in development)

LUPEROX® DDM-9 RED

Exposure during pregnancy. inhalation (rat) / No birth defects were observed. (delays in development, at doses that produce effects in mothers)

Reproductive effects

Reproduction test. drinking water (rat) / No toxicity to reproduction / (similar material)

Human experience

Inhalation:

Upper respiratory tract: irritation. (vapor)

Central nervous system: drowsiness, dizziness. Exposure to other materials makes the association questionable. (based on reports of occupational exposure to workers)

Nervous system: altered reflexes, changes in motor activity. Exposure to other materials makes the association questionable. (based on reports of occupational exposure to workers)

Human experience

Skin contact:

Skin: No skin allergy was observed. (studied using human volunteers)

Skin: dermatitis, cracking. Has a degreasing effect on the skin. (repeated or prolonged exposure)

Human experience

Eye contact:

Eyes: irritating. (vapor)

12. ECOLOGICAL INFORMATION

Chemical Fate and Pathway

Data on this material and/or its components are summarized below.

Data for Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester (6846-50-0)

Biodegradation:

Inherently biodegradable. (aerobic, 28 d) biodegradation 71 % / The 10 day time window criterion is not fulfilled.

Theoretical Biological Oxygen Demand:

Theoretical oxygen demand (ThOD) = 2,400 mg/g

Bioaccumulation:

BCF = 670 (without metabolism)

BCF = 14,611 (with metabolism)

BCF = 5.2 - 31 (Carp)

Octanol Water Partition Coefficient:

log Pow: = 4.04 - 4.91 (Method: calculated)

Data for 2-Butanone, peroxide (1338-23-4)

LUPEROX® DDM-9 RED

Biodegradation:

Readily biodegradable. (28 d) biodegradation 87 % / OECD guideline 301D (Closed bottle test)

Octanol Water Partition Coefficient:

log Pow: < 0.3, at 77 °F (25 °C) (Method: OECD Test Guideline 117)

Data for 2,4-Pentandiol, 2-methyl- (107-41-5)

Biodegradation:

Readily biodegradable. (28 d) biodegradation 81 % / OECD Test Guideline 301 F

Octanol Water Partition Coefficient:

log Pow: = -0.14(Method: calculated)

Data for 2-Butanone (78-93-3)

Biodegradation:

Readily biodegradable. (28 d) biodegradation 98 % / OECD Test Guideline 301 D

Octanol Water Partition Coefficient:

log Pow: = 0.3

Photodegradation:

Half-life direct photolysis: = 6.9 d
(is rapidly degraded in air by OH radicals.)

Ecotoxicology

Data on this material and/or its components are summarized below.

Data for Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester (6846-50-0)

Aquatic toxicity data:

No effect up to the limit of solubility. Lepomis macrochirus (Bluegill sunfish) 96 h NOEC > 6 mg/l

Aquatic invertebrates:

No effect up to the limit of solubility. Daphnia magna (Water flea) 48 h EC50 > 1.46 mg/l

Algae:

No effect up to the limit of solubility. Selenastrum capricornutum 72 h EC50 (growth rate) > 7.49 mg/l

Chronic toxicity to aquatic invertebrates:

Harmful. Daphnia magna (Water flea) 21 d NOEC (reproduction) = 0.7 mg/l

Data for 2-Butanone, peroxide (1338-23-4)

Aquatic toxicity data:

Harmful. Poecilia reticulata (guppy) 96 h LC50 = 44.2 mg/l (In solution in Dimethyl phthalate)

Aquatic invertebrates:

Harmful. Daphnia (water flea) 48 h EC50 = 39 mg/l (In solution in Dimethyl phthalate)

Algae:

Toxic. Pseudokirchneriella subcapitata (green algae) 72 h ErC50 = 5.6 mg/l (In solution in Dimethyl phthalate)

LUPEROX® DDM-9 RED**Microorganisms:**

Respiration inhibition / Activated sludge 30 min EC50 = 48 mg/l (In solution in Dimethyl phthalate)

Data for 2,4-Pentanediol, 2-methyl- (107-41-5)**Aquatic toxicity data:**

Practically nontoxic. *Gambusia affinis* (Mosquito fish) 96 h LC50 = 8,510 mg/l

Aquatic invertebrates:

Practically nontoxic. *Daphnia magna* (Water flea) 48 h EC50 = 5,410 mg/l

Algae:

Practically nontoxic. *Selenastrum capricornutum* 72 h EC50 > 429 mg/l

Microorganisms:

Practically nontoxic. Bacteria 10 d NOEC > 1,000 mg/l

Chronic toxicity to aquatic plants:

Practically nontoxic. *Pseudokirchneriella subcapitata* (green algae) 72 d NOEC = 429 mg/l

Data for 2-Butanone (78-93-3)**Aquatic toxicity data:**

Practically nontoxic. *Pimephales promelas* (fathead minnow) 96 h LC50 = 3,200 mg/l

Aquatic invertebrates:

Practically nontoxic. *Daphnia magna* (Water flea) 48 h EC50 = 308 mg/l

Algae:

Practically nontoxic. *Pseudokirchneriella subcapitata* (green algae) 72 h EC50 = 1,972 mg/l

Microorganisms:

Pseudomonas putida 16 h Toxicity threshold = 1,150 mg/l

13. DISPOSAL CONSIDERATIONS**Waste disposal:**

Dilution followed by incineration is the preferred method. Dilution ratio of 10:1 in a clean, compatible, combustible solvent (i.e., Fuel Oil #2, mineral oil) will reduce reactivity hazard during incineration and transportation. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

Take appropriate measures to prevent release to the environment.

LUPEROX® DDM-9 RED
14. TRANSPORT INFORMATION
US Department of Transportation (DOT)

UN Number : 3105
Proper shipping name : Organic peroxide type D, liquid
Technical name : (Methyl ethyl ketone peroxide(s), <= 45%)
Class : 5.2
Marine pollutant : no
Reportable quantity : 10 lbs (Methyl ethyl ketone peroxide(s))

International Maritime Dangerous Goods Code (IMDG)

UN Number : 3105
Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID
Technical name : (METHY ETHYL KETONE PEROXIDE, <= 45%)
Class : 5.2
Marine pollutant : no
Flash point : 180 °F (82 °C) Setaflash closed cup

15. REGULATORY INFORMATION
Chemical Inventory Status

United States TSCA Inventory	TSCA	The components of this product are all on the TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Conforms to
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform
Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Conforms to
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	PICCS (PH)	Conforms to
Australia Inventory of Chemical Substances (AICS)	AICS	Does not conform

United States – Federal Regulations
SARA Title III – Section 302 Extremely Hazardous Chemicals:

<u>Chemical name</u>	<u>CAS-No.</u>	<u>SARA Reportable Quantities</u>	<u>SARA Threshold Planning Quantity</u>
----------------------	----------------	-----------------------------------	---

LUPEROX® DDM-9 RED

Hydrogen peroxide	7722-84-1	1000 lbs	1000 lbs
-------------------	-----------	----------	----------

SARA Title III - Section 311/312 Hazard Categories:

Acute Health Hazard, Reactivity Hazard, Fire Hazard

SARA Title III – Section 313 Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

<u>Chemical name</u>	<u>CAS-No.</u>	<u>Reportable quantity</u>
2-Butanone, peroxide	1338-23-4	10 lbs
2-Butanone	78-93-3	5000 lbs

United States – State Regulations
New Jersey Right to Know

<u>Chemical name</u>	<u>CAS-No.</u>
2-Butanone, peroxide	1338-23-4
2,4-Pentanediol, 2-methyl-	107-41-5
2-Butanone	78-93-3

New Jersey Right to Know – Special Health Hazard Substance(s)

<u>Chemical name</u>	<u>CAS-No.</u>
2-Butanone, peroxide	1338-23-4

LUPEROX® DDM-9 RED

2-Butanone 78-93-3

Pennsylvania Right to Know

<u>Chemical name</u>	<u>CAS-No.</u>
Propanoic acid, 2-methyl-, 2,2-dimethyl-1-(1-methylethyl)-1,3-propanediyl ester	6846-50-0

2-Butanone, peroxide 1338-23-4

2,4-Pentanediol, 2-methyl- 107-41-5

2-Butanone 78-93-3

Hydrogen peroxide 7722-84-1

Xylene 1330-20-7

Pennsylvania Right to Know – Environmentally Hazardous Substance(s)

<u>Chemical name</u>	<u>CAS-No.</u>
2-Butanone, peroxide	1338-23-4
2-Butanone	78-93-3
Hydrogen peroxide	7722-84-1
Xylene	1330-20-7

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

<u>Chemical name</u>	<u>CAS-No.</u>
Benzene, ethyl-	100-41-4

16. OTHER INFORMATION

LUPEROX® DDM-9 RED

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H227	Combustible liquid.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Miscellaneous:

Other information: Refer to National Fire Protection Association (NFPA) Codes 30, 70, 77, and 497 and OSHA 29 CFR 1910.106, for safe handling.

Latest Revision(s):

Reference number: 200013962
Date of Revision: 02/02/2018
Date Printed: 02/02/2018

LUPEROX® is a registered trademark of Arkema Inc.

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, ARKEMA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN.** The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement. See SDS for Health & Safety Considerations.

Arkema has implemented a Medical Policy regarding the use of Arkema products in Medical Devices applications that are in contact with the body or circulating bodily fluids (<http://www.arkema.com/en/social-responsibility/responsible-product-management/medical-device-policy/index.html>) Arkema has designated Medical grades to be used for such Medical Device applications. Products that have not been designated as Medical grades are not authorized by Arkema for use in Medical Device applications that are in contact with the body or circulating bodily fluids. In addition, Arkema strictly prohibits the use of any Arkema products in Medical Device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Arkema trademarks and the Arkema name shall not be used in conjunction with customers' medical devices, including without limitation, permanent or temporary implantable devices, and customers shall not represent to anyone else, that Arkema allows, endorses or permits the use of Arkema products in such medical devices.

It is the sole responsibility of the manufacturer of the medical device to determine the suitability (including biocompatibility) of all raw materials, products and components, including any medical grade Arkema products, in order to ensure that the final end-use product is safe for its end use; performs or functions as intended; and complies with all applicable legal and regulatory requirements (FDA or other national drug agencies) It is the sole responsibility of the manufacturer of the medical device to conduct all necessary tests and inspections and to evaluate the medical device under actual end-use requirements and to adequately advise and warn purchasers, users, and/or learned intermediaries (such as physicians) of pertinent risks and fulfill any postmarket surveillance obligations. Any decision regarding the appropriateness of a particular Arkema material in a particular medical device should be based on the judgment of the manufacturer, seller, the competent authority, and the treating physician.