

CORDURA NYLON DWR URETHANE COATED 500 DENIER MODEL #: F-2255-60

| TEST UNIT OF MEASURE | TEST METHOD | TEST RESULTS |
|-------------------------|------------------|-----------------|
| WEIGHT (OZ/SQ YD) | FTM 5041 | 7.35oz |
| WIDTH (INCHES) | VISUAL | 60" |
| WEAVE | VISUAL | Plain |
| YARN COUNT (IN) | VISUAL | 50 x 36 |
| GRAB TENSILE (LBS) | FTM 5100 | 300 x 225 |
| CROCKING | AATCC-8 | 5 DRY/ 4 Wet |
| Spray Rating | AATCC-22 | |
| Colorfastness to: | | |
| Laundering | AATCC-61 - 1A | 4.04.0 |
| Light | AATCC-16 | |



Information and data included in this data sheet is considered to be accurate and reliable to the best of our knowledge however it is not quaranteed to be so. It is the user/buyer's responsibility to determine for themselves the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. Composite Envisions make no representations or warranties as to the results to be obtained in using any material. As Composite Envisions cannot foresee all conditions under which products will be used, user/buyer waives any claim against Composite Envisions for direct, indirect, consequential, or exemplary damages including without limitation, damage which may incur as a result of user/buyer's use or misuse of the product or the product's failure to perform to any expected performance level.

Composite Envisions LLC 8450 Development Court Wausau, WI 54401 USA +1 715-842-0101 info@compositeenvisions.com https://compositeenvisions.com/

