

Product Data Sheet

Fabric Construction

Fibre Type: E-Glass

Construction: +45/-45

Fabric Weight: 609 gsm +/- 5%

Stitching Fibre

Stitching Thread: Texturised Polyester

Stitch DTex: 78

Stitch Gauge: 6.0 gg

Stitch Length: 2.5 mm

Stitch Type: Pillar

Stitch Weight: 7 gsm


Ply Construction

Layer 2: +45º

Fibre Specification: E-Glass
Fibre Tex: 300 tex
Gauge: 18 gg
Ply Weight: 301 gsm

Layer 1: -45º

Fibre Specification: E-Glass
Fibre Tex: 300 tex
Gauge: 18 gg
Ply Weight: 301 gsm



Customisation

Customer Code and Description: Customer Specified

Fabric Width: 1270mm (+/- 5mm) - or tapes on application

Tracer Threads / Tapered Edges: Customer Specified

Approved Fibres: On Application

Roll Weight / Length: Customer Specified
Cardboard Core: Customer Specified
Packaging: Customer Specified

For more information

Hexcel is a worldwide supplier of composite materials to aerospace and industrial markets. Our comprehensive range includes:

- HexTow® carbon fibres
- HexForce® reinforcements
- HiMax[™] non-crimp fabrics

• HexMC® moulding compounds

- HexPly® prepregs
- HexFlow® RTM resins
- Redux® adhesives
- HexTool® tooling materials Engineered core
- HexWeb® honeycombs
- · Acousti-Cap® sound attenuating honeycomb
- · Engineered products