




## HEXCEL HIMAX FIBERGLASS E-GLASS FABRIC BIAXIAL +45°/-45° MODEL #: F-2409-50

### FABRIC CONSTRUCTION

Fibre Type:	E-Glass
Construction:	+45/-45
Fabric Weight:	808 gsm +/- 5%

### STITCHING FIBRE

Stitching Thread:	Texturised Polyester W
Stitch DTex:	78
Stitch Gauge:	6.0 gg
Stitch Length:	3.3 mm
Stitch Type:	Pillar
Stitch Weight:	6 gsm



### PLY CONSTRUCTION

<i>Layer 2: +45 ply</i>		<i>Layer 1: -45 ply</i>	
Fibre Specification:	E-Glass	Fibre Specification:	E-Glass
Fibre Tex:	600 tex	Fibre Tex:	600 tex
Gauge:	12 gg	Gauge:	12 gg
Ply Weight:	401 gsm	Ply Weight:	401 gsm

Information and data included in this data sheet is considered to be accurate and reliable to the best of our knowledge however it is not guaranteed to be so. It is the user/buyer's responsibility to determine for themselves the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. Composite Envisions make no representations or warranties as to the results to be obtained in using any material. As Composite Envisions cannot foresee all conditions under which products will be used, user/buyer waives any claim against Composite Envisions for direct, indirect, consequential, or exemplary damages including without limitation, damage which may incur as a result of user/buyer's use or misuse of the product or the product's failure to perform to any expected performance level.

Composite Envisions LLC  
8450 Development Court  
Wausau, WI 54401 USA  
+1 715-842-0101  
info@compositeenvisions.com  
<https://compositeenvisions.com/>



# COMPOSITE ENVISIONS