5700 Skylab Road Huntington Beach CA 92647 USA Phone: +1 714-899-8100 Fax: +1 714-899-8179 E-mail: airtech@airtechintl.com Website: www.airtechonline.com

Data Sheet

GS-43MR

High tack and high temperature sealant tape

DESCRIPTION

GS-43MR is our premium sealant tape with excellent tack and easy clean-up. It is usable up to 450°F (232°C).

BENEFITS

- Excellent tack level, so vacuum bagging is easier and safer.
- High temperature rating for safer high temperature cures.
- Approved on aerospace specifications worldwide.

TECHNICAL DATA

Color Off-white

Base material Synthetic rubber Maximum use temperature 450°F (232°C)

Shelf life 12 months from date of manufacture

Storage conditions

Tape must be stored flat in original packaging at 72°F (22°C)

Do not refrigerate

SIZES

Dimensions	Packaging
1/8 inch x 1/2 inch x 25 feet (3 mm x 12 mm x 7.5m)	40 rolls per case
1/8 inch x 3/4 inch x 25 feet (3 mm x 19 mm x 7.5 m)	28 rolls per case



NOTES

- For clean removal, it is recommended to strip the tape from the mold surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated: 2015-08-21

Catalog position: Vacuum bag sealant tapes