

PRECISION FABRICS GROUP

Code: 4819 | Style: 700-00005

Code: 4822 | Style: 100-00000

Polyester Bleeder | Breather

Code 4819 and 4822 are 100% non-apertured, nonwoven fabric. Both exhibit outstanding elongation drapability and high stretch properties. These high stretch and absorptive qualities reduce bridging on complex contoured surfaces. Code 4819 and 4822 properties are recommended where multiple layers are needed to achieve the proper resin-to-fiber ratio. Code 4819 and 4822 are not release fabrics and should be used with a suitable Precision Fabrics peel ply release fabric. Code 4819 and 4822 have melting points of approximately 480°F (249°C). Code 4819 and 4822 are available in precision slit widths down to 1 inch.

	Codes	US	Metric	
WIDTH	4819 4822	48, 72, 144 in 48 in	122, 183, 366 cm 122 cm	nominal
WEIGHT	4819 4822	2.0 oz/yd ² 1.2 oz/yd ²	68 g/m ² 40 g/m ²	nominal
THICKNESS	4819 4822	20 mils 10 mils	0.51 mm 0.25 mm	nominal
MD GRAB TENSILE	4819 4822	51 lbs 28 lbs	227 Newtons 102 Newtons	nominal
XD GRAB TENSILE	4819 4822	26 lbs 15 lbs	115 Newtons 67 Newtons	nominal
ROLL LENGTHS	4819 4822	250 yd 250 yd	229 m 229 m	nominal

The information is not to be construed as a specification or a license to operate under, nor is it intended to suggest infringement of any existing patents. We believe the information in the bulletin is correct. No warranty of accuracy is implied.

PrecisionFabricsGroup

engineered materials & technical fabrics

301 North Elm Street | Greensboro, NC 27401

1.888.733.5759 | 336.510.8000

precisionfabrics.com