

**PRO-SET® LAM-226 Hardener****Safety Data Sheet**

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 04/13/2015

Revision date: 01/25/2019

Version: LAM-226 -2019a

**SECTION 1: Identification****Identification**

**Product form** : Mixtures  
**Product name** : PRO-SET® LAM-226 Hardener  
**Product code** : LAM-226, LAM-226-1, LAM-226-2, LAM-226-3, LAM-226-4, LAM-226-5

**Relevant identified uses of the substance or mixture and uses advised against**

**Recommended use** : Curing agent for epoxy resins

**Details of the supplier of the safety data sheet****Manufacturer**

Gougeon Brothers, Inc  
 100 Patterson Ave.  
 Bay City, MI 48706 - U.S.A.  
 T 888-377-6738 or 989-684-7286  
[www.prosetepoxy.com](http://www.prosetepoxy.com)

**Emergency telephone number**

**Emergency number** : CHEMTREC 1 (800) 424-9300  
 CHEMTREC International +1 (703) 527-3887 24 hr

**SECTION 2: Hazard(s) identification****Classification of the substance or mixture**

Acute Tox. 4 (Oral)  
 Acute Tox. 4 (Dermal)  
 Skin Corr. 1B  
 Eye Dam. 1  
 Skin Sens. 1  
 Repr. 2  
 STOT RE 2  
 Aquatic Acute 2  
 Aquatic Chronic 2

**Label elements****Hazard pictograms (GHS)****Signal word (GHS)**

Danger

**Hazard statements (GHS)**

Harmful if swallowed or in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure if swallowed. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

**Precautionary statements (GHS)**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust, fume, gas, mist, vapours, spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves, protective clothing, eye protection, face protection. If swallowed: rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Collect spillage. Store locked up. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

# PRO-SET® LAM-226 Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### Other hazards

No additional information available

### Unknown acute toxicity

No additional information available

## SECTION 3: Composition/information on ingredients

### Substance

Not applicable

### Mixtures

| Name   | Product identifier   | HPR %   |
|--|----------------------|---------|
| Propylene glycol diamine, 2-amino-, diether with Propylene   | (CAS No) 9046-10-0   | 10 - 30 |
| Isophorone diamine   | (CAS No) 2855-13-2   | 10 - 30 |
| Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-(2-aminomethylethoxy)-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) | (CAS No) 39423-51-3  | 5 - 13  |
| Formaldehyde, polymer with benzenamine, hydrogenated   | (CAS No) 135108-88-2 | 5 - 13  |
| 1-Piperazineethanamine   | (CAS No) 140-31-8    | 5 - 10  |
| Cyclohexanamine, 4,4'-methylenebis-  | (CAS No) 1761-71-3   | 3 - 10  |
| 1,3-Propanediamine, N,N"-1,2-ethanediylbis-  | (CAS No) 10563-26-5  | 5 - 10  |
| 4-tert-Butylphenol   | (CAS No) 98-54-4     | 3 - 7   |
| 1,3-Benzenedimethanamine   | (CAS No) 1477-55-0   | 3 - 7   |
| Trimethylhexamethylenediamine  | (CAS No) 25620-58-0  | 1 - 5   |
| Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)   | (CAS No) 57214-10-5  | 1 - 5   |
| Phenol, 4-nonyl-, branched   | (CAS No) 84852-15-3  | 0.1 - 1 |

The exact chemical identity and/or exact percentage (concentration) of each ingredient may be held as confidential business information (CBI). Any ingredient not disclosed in this section may have been determined not to be hazardous to health or the environment, or it may be present at a level below its disclosure threshold.

## SECTION 4: First aid measures

### Description of first aid measures

#### First-aid measures after inhalation

: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

#### First-aid measures after skin contact

: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or doctor/physician.

#### First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

#### First-aid measures after ingestion

: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

### Most important symptoms and effects, both acute and delayed

#### Symptoms/injuries after inhalation

: May cause respiratory tract irritation.

#### Symptoms/injuries after skin contact

: Harmful in contact with skin. Causes severe burns. Symptoms may include redness, pain, blisters. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction.

#### Symptoms/injuries after eye contact

: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.

#### Symptoms/injuries after ingestion

: Harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause stomach distress, nausea or vomiting.

### Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media

: Foam. Carbon dioxide. Dry chemical.

#### Unsuitable extinguishing media

: Do not use a heavy water stream.

# PRO-SET® LAM-226 Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### Special hazards arising from the substance or mixture

- Fire hazard** : Products of combustion may include, and are not limited to: oxides of carbon, nitrogen oxides, amines, ammonia, nitric acid, cyanides, aldehydes, nitrosamines. When mixed with sawdust, wood chips, or other cellulosic material, spontaneous combustion can occur under certain conditions. Heat is generated as the air oxidizes the amine. If the heat is not dissipated quickly enough, it can ignite the sawdust.
- Reactivity** : No dangerous reaction known under conditions of normal use.
- Advice for firefighters**
- Protection during firefighting** : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

- General measures** : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### For non-emergency personnel

No additional information available

#### For emergency responders

No additional information available

#### Environmental precautions

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

#### Methods and material for containment and cleaning up

- For containment** : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). Do not absorb in sawdust, paper, cloth or other combustible absorbents.
- Methods for cleaning up** : Scoop up material and place in a disposal container. Provide ventilation.

#### Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

### SECTION 7: Handling and storage

#### Precautions for safe handling

- Precautions for safe handling** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe dust, fume, gas, mist, vapours, spray. Do not swallow. Handle and open container with care. Do not eat, drink or smoke when using this product. Use personal protective equipment as required. When mixed with epoxy resin this product causes an exothermic reaction, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapors that vary widely in composition and toxicity.

- Hygiene measures** : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking. Contaminated work clothing should not be allowed out of the workplace.

#### Conditions for safe storage, including any incompatibilities

- Storage conditions** : Keep out of the reach of children. Keep container tightly closed. Store in dry, cool, well-ventilated area. Protect from moisture. Storage temperature : 40°F (4°C) - 90°F (32°C).

### SECTION 8: Exposure controls/personal protection

#### Control parameters

|  |
|--|
| <b>Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)</b>  |
| Not applicable   |
| <b>Isophorone diamine (2855-13-2)</b>  |
| Not applicable   |
| <b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro.-omega.-(2-aminomethylethoxy)-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) (39423-51-3)</b> |
| Not applicable   |

# PRO-SET® LAM-226 Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

|  |  |                       |
|--|--|-----------------------|
| <b>Formaldehyde, polymer with benzenamine, hydrogenated (135108-88-2)</b>                                  |  |                       |
| Not applicable   |  |                       |
| <b>1-Piperazineethanamine (140-31-8)</b>   |  |                       |
| Not applicable   |  |                       |
| <b>Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)</b>   |  |                       |
| Not applicable   |  |                       |
| <b>1,3-Propanediamine, N,N''-1,2-ethanediybis- (10563-26-5)</b>  |  |                       |
| Not applicable   |  |                       |
| <b>4-tert-Butylphenol (98-54-4)</b>  |  |                       |
| Not applicable   |  |                       |
| <b>1,3-Benzenedimethanamine (1477-55-0)</b>  |  |                       |
| ACGIH  | ACGIH Ceiling (mg/m <sup>3</sup> )       | 0.1 mg/m <sup>3</sup> |
| NIOSH  | NIOSH REL (ceiling) (mg/m <sup>3</sup> ) | 0.1 mg/m <sup>3</sup> |
| <b>Trimethylhexamethylenediamine (25620-58-0)</b>  |  |                       |
| Not applicable   |  |                       |
| <b>Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine) (57214-10-5)</b> |  |                       |
| Not applicable   |  |                       |
| <b>Phenol, 4-nonyl-, branched (84852-15-3)</b>   |  |                       |
| Not applicable   |  |                       |

### Exposure controls

#### Appropriate engineering controls

: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

#### Hand protection

: Wear chemically resistant protective gloves.

#### Eye protection

: Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

#### Skin and body protection

: Wear suitable protective clothing.

#### Respiratory protection

: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### Environmental exposure controls

: Maintain levels below Community environmental protection thresholds.

#### Other information

: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

|   |  |
|---|--|
| <b>Physical state</b>                             | : Liquid   |
| <b>Appearance</b>                                 | : No data available  |
| <b>Colour</b>                                     | : Amber  |
| <b>Odour</b>                                      | : Ammonia  |
| <b>Odour threshold</b>                            | : No data available  |
| <b>pH</b>   | : >11 and <12.5 (estimated based on ingredient data)           |
| <b>Melting point</b>                              | : No data available  |
| <b>Freezing point</b>                             | : No data available  |
| <b>Boiling point</b>                              | : > 400 °F (204°C) estimated based on similar product.         |
| <b>Flash point</b>                                | : > 200 °F (93°C) estimated based similar product.             |
| <b>Relative evaporation rate (butylacetate=1)</b> | : No data available  |
| <b>Flammability (solid, gas)</b>                  | : Not flammable  |
| <b>Vapour pressure</b>                            | : < 1 mm Hg @ 20°C / 68°F (estimated based on ingredient data) |
| <b>Relative vapour density at 20 °C</b>           | : No data available  |
| <b>Relative density</b>                           | : 0.97   |

# PRO-SET® LAM-226 Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

|  |  |
|--|--|
| <b>Solubility</b>                            | : Appreciable  |
| <b>Partition coefficient n-octanol/water</b> | : No data available  |
| <b>Auto-ignition temperature</b>             | : No data available  |
| <b>Decomposition temperature</b>             | : No data available  |
| <b>Viscosity, kinematic</b>                  | : 16.2 mm <sup>2</sup> /s @ 40°C / 104°F   |
| <b>Viscosity, dynamic</b>                    | : No data available  |
| <b>Explosive limits</b>                      | : No data available  |
| <b>Explosive properties</b>                  | : No data available  |
| <b>Oxidising properties</b>                  | : No data available  |
| <b>Other information</b>                     |  |
| <b>VOC content</b>                           | : LAM-125 / LAM-226: 3.14 g/L (0.03 lbs/gal); LAM-135 / LAM-226: 1.20 g/L (0.01 lbs/gal); LAM-145 / LAM-226: 1.35 g/L (0.01 lbs/gal) |
| <b>Bulk density</b>                          | : 8.15 lb/gal (0.97 kg/L)  |

### SECTION 10: Stability and reactivity

|   |   |
|---|---|
| <b>Reactivity</b>                         | : No dangerous reaction known under conditions of normal use.   |
| <b>Chemical stability</b>                 | : Stable under normal storage conditions.   |
| <b>Possibility of hazardous reactions</b> | : No dangerous reaction known under conditions of normal use. A mass of more than one pound of product plus an epoxy resin will cause irreversible polymerization with significant heat buildup and pressure. |
| <b>Conditions to avoid</b>                | : Heat. Incompatible materials.   |
| <b>Incompatible materials</b>             | : Acids. Oxidizing materials. Halogenated compounds.  |
| <b>Hazardous decomposition products</b>   | : May include, and are not limited to: oxides of carbon, nitrogen oxides, amines, ammonia, nitric acid, cyanides, aldehydes, nitrosamines, phenolics.   |

### SECTION 11: Toxicological information

#### Information on toxicological effects

| Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0) |                |
|--|----------------|
| LD50 oral rat  | 2855 mg/kg     |
| LD50 dermal rabbit   | 2890 mg/kg     |
| LC50 inhalation rat  | > 0.74 mg/l/8h |

| Isophorone diamine (2855-13-2) |                |
|--------------------------------|----------------|
| LD50 oral rat                  | 1030 mg/kg     |
| LD50 dermal rabbit             | > 2000 mg/kg   |
| LC50 inhalation rat            | > 5.01 mg/l/4h |

| Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro.-omega.-(2-aminomethylethoxy)-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) (39423-51-3) |              |
|---|--------------|
| LD50 oral rat   | 550 mg/kg    |
| LD50 dermal rabbit  | > 1000 mg/kg |

| 1-Piperazineethanamine (140-31-8) |            |
|-----------------------------------|------------|
| LD50 oral rat                     | 2097 mg/kg |
| LD50 dermal rabbit                | 866 mg/kg  |

| Cyclohexanamine, 4,4'-methylenebis- (1761-71-3) |              |
|---|--------------|
| LD50 oral rat                                   | 380 mg/kg    |
| LD50 dermal rabbit                              | > 1000 mg/kg |

| 1,3-Propanediamine, N,N''-1,2-ethanediylbis- (10563-26-5) |                 |
|---|-----------------|
| LD50 oral rat   | 1200 mg/kg      |
| LD50 dermal rabbit  | 190 - 210 mg/kg |

| 4-tert-Butylphenol (98-54-4) |   |
|------------------------------|---|
| LD50 oral rat                | > 2000 mg/kg  |
| LD50 dermal rat              | No data. Intraperitoneal – mouse – 78 mg/kg.                                      |
| LC50 inhalation rat          | 5.6 mg/l Remarks: Nutritional and Metabolic: Weight loss or decreased weight gain |

# PRO-SET® LAM-226 Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| 1,3-Benzenedimethanamine (1477-55-0) |              |
|--------------------------------------|--------------|
| LD50 oral rat                        | 980 mg/kg    |
| LD50 dermal rabbit                   | 2000 mg/kg   |
| LC50 inhalation rat                  | 1.34 mg/l/4h |

| Trimethylhexamethylenediamine (25620-58-0) |           |
|--|-----------|
| LD50 oral rat                              | 910 mg/kg |

| Phenol, 4-nonyl-, branched (84852-15-3) |            |
|---|------------|
| LD50 oral rat                           | 1412 mg/kg |

|  |   |
|--|---|
| <b>Acute toxicity (oral)</b>             | : Oral: Harmful if swallowed.   |
| <b>Acute toxicity (dermal)</b>           | : Dermal: Harmful in contact with skin.   |
| <b>Acute toxicity (inhalation)</b>       | : Not classified.   |
| <b>Skin corrosion/irritation</b>         | : Causes severe skin burns  |
| <b>Serious eye damage/irritation</b>     | : Causes serious eye damage.  |
| <b>Respiratory or skin sensitization</b> | : May cause an allergic skin reaction.  |
| <b>Germ cell mutagenicity</b>            | : Not classified.   |
| <b>Carcinogenicity</b>                   | : Not classified.   |
| <b>Reproductive toxicity</b>             | : Suspected of damaging fertility or the unborn child.                            |
| <b>STOT-single exposure</b>              | : Not classified.   |
| <b>STOT-repeated exposure</b>            | : May cause damage to organs through prolonged or repeated exposure if swallowed. |
| <b>Aspiration hazard</b>                 | : Not classified.   |

| PRO-SET® LAM-226 Hardener                               |                         |
|---|-------------------------|
| Viscosity, kinematic (calculated value) (40 °C /104 °F) | 16.2 mm <sup>2</sup> /s |

|  |   |
|--|---|
| <b>Potential adverse human health effects and symptoms</b> | : Harmful in contact with skin. Harmful if swallowed.   |
| <b>Symptoms/injuries after inhalation</b>                  | : May cause respiratory tract irritation.   |
| <b>Symptoms/injuries after skin contact</b>                | : Harmful in contact with skin. Causes severe burns. Symptoms may include redness, pain, blisters. Repeated exposure to this material can result in absorption through skin causing significant health hazard. May cause an allergic skin reaction. |
| <b>Symptoms/injuries after eye contact</b>                 | : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.  |
| <b>Symptoms/injuries after ingestion</b>                   | : Harmful if swallowed. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. May cause stomach distress, nausea or vomiting.  |
| <b>Other information</b>                                   | : Likely routes of exposure: ingestion, inhalation, skin and eye.   |

## SECTION 12: Ecological information

### Toxicity

**Ecology - general** : Toxic to aquatic life with long lasting effects.

| Isophorone diamine (2855-13-2) |   |
|--------------------------------|---|
| EC50 Daphnia 1                 | 14.6 - 21.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [semi-static]) |

| 1-Piperazineethanamine (140-31-8) |  |
|-----------------------------------|--|
| LC50 fish 1                       | 1950 - 2460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1                    | 32 mg/l (Exposure time: 48 h - Species: Daphnia magna)                               |
| LC50 fish 2                       | > 1000 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])       |

| 4-tert-Butylphenol (98-54-4) |  |
|------------------------------|--|
| LC50 fish 1                  | 4.71 - 5.62 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1               | 3.9 mg/l (Exposure time: 48 h - Species: Daphnia magna)                              |
| LC50 fish 2                  | 6.9 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])                   |
| EC50 Daphnia 2               | 3.4 - 4.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])               |

| Phenol, 4-nonyl-, branched (84852-15-3) |  |
|---|--|
| LC50 fish 1                             | 0.135 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |

# PRO-SET® LAM-226 Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

|  |   |
|--|---|
| <b>Phenol, 4-nonyl-, branched (84852-15-3)</b> |   |
| EC50 Daphnia 1                                 | 0.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)                        |
| LC50 fish 2                                    | 0.1351 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through]) |

### Persistence and degradability

|                                  |                  |
|----------------------------------|------------------|
| <b>PRO-SET® LAM-226 Hardener</b> |                  |
| Persistence and degradability    | Not established. |

### Bioaccumulative potential

|                                  |                  |
|----------------------------------|------------------|
| <b>PRO-SET® LAM-226 Hardener</b> |                  |
| Bioaccumulative potential        | Not established. |

|                                       |                 |
|---------------------------------------|-----------------|
| <b>Isophorone diamine (2855-13-2)</b> |                 |
| Partition coefficient n-octanol/water | 0.79 (at 23 °C) |

|  |                               |
|--|-------------------------------|
| <b>1-Piperazineethanamine (140-31-8)</b> |                               |
| BCF fish 1                               | (no bioaccumulation expected) |
| Partition coefficient n-octanol/water    | -1.48                         |

|  |      |
|--|------|
| <b>Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)</b> |      |
| Partition coefficient n-octanol/water                  | 2.03 |

|                                       |          |
|---------------------------------------|----------|
| <b>4-tert-Butylphenol (98-54-4)</b>   |          |
| BCF fish 1                            | 34 - 240 |
| Partition coefficient n-octanol/water | 2.44     |

|   |                 |
|---|-----------------|
| <b>Trimethylhexamethylenediamine (25620-58-0)</b> |                 |
| Partition coefficient n-octanol/water             | 0.77 (at 23 °C) |

|  |     |
|--|-----|
| <b>Phenol, 4-nonyl-, branched (84852-15-3)</b> |     |
| BCF fish 1                                     | 271 |

### Mobility in soil

|                                  |                                      |
|----------------------------------|--------------------------------------|
| <b>PRO-SET® LAM-226 Hardener</b> |                                      |
| Ecology - soil                   | No additional information available. |

### Other adverse effects

**Effect on the global warming** : No known effects from this product.

| Ingredient   | CAS#        | Ecotoxicity Classification Information       |
|--|-------------|--|
| Propylene glycol diamine, 2-amino-, diether with Propylene   | 9046-10-0   | Acute Aquatic Cat. 3; Chronic Aquatic Cat. 2 |
| Isophorone diamine   | 2855-13-2   | Acute Aquatic Cat. 3; Chronic Aquatic Cat. 3 |
| Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-(2-aminomethylethoxy)-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) | 39423-51-3  | Acute Aquatic Cat. 2; Chronic Aquatic Cat. 2 |
| Formaldehyde, polymer with benzenamine, hydrogenated   | 135108-88-2 | Not classified                               |
| 1-Piperazineethanamine   | 140-31-8    | Acute Aquatic Cat. 3; Chronic Aquatic Cat. 3 |
| Cyclohexanamine, 4,4'-methylenebis-  | 1761-71-3   | Acute Aquatic Cat. 2; Chronic Aquatic Cat. 2 |
| 1,3-Propanediamine, N,N"-1,2-ethanediylbis-  | 10563-26-5  | Not classified                               |
| 4-tert-Butylphenol   | 98-54-4     | Acute Aquatic Cat. 2; Chronic Aquatic Cat. 2 |
| 1,3-Benzenedimethanamine   | 1477-55-0   | Acute Aquatic Cat. 3; Chronic Aquatic Cat. 3 |
| Trimethylhexamethylenediamine  | 25620-58-0  | Acute Aquatic Cat. 3; Chronic Aquatic Cat. 3 |
| Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine)   | 57214-10-5  | Acute Aquatic Cat. 1; Chronic Aquatic Cat. 1 |
| Phenol, 4-nonyl-, branched   | 84852-15-3  | Acute Aquatic Cat. 1; Chronic Aquatic Cat. 1 |

**Other information** : Avoid release to the environment.

## SECTION 13: Disposal considerations

### Waste treatment methods

**Product/Packaging disposal recommendations** : Avoid release to the environment. This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

# PRO-SET® LAM-226 Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 14: Transport information

#### Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT and TDG

|                                |  |
|--------------------------------|--|
| UN-No. (DOT/TDG)               | : UN2735   |
| Proper Shipping Name (DOT/TDG) | : Polyamines, liquid, corrosive, n.o.s. (Isophorone diamine) |
| Class (DOT/TDG)                | : 8  |
| Packing group (DOT/TDG)        | : II   |
| Marine Pollutant               | : No   |

#### Transport by sea

In accordance with IMDG

|                             |  |
|-----------------------------|--|
| UN-No. (IMDG)               | : 2735   |
| Proper Shipping Name (IMDG) | : POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Isophorone diamine) |
| Class (IMDG)                | : 8  |
| Packing group (IMDG)        | : II   |
| EmS Number                  | : F-A, S-B   |
| Marine pollutant            | : Yes  |

#### Transport by sea

In accordance with IATA

|                             |  |
|-----------------------------|--|
| UN-No. (IATA)               | : 2735   |
| Proper Shipping Name (IATA) | : Polyamines, liquid, corrosive, n.o.s. (Isophorone diamine) |
| Class (IATA)                | : 8  |
| Packing group (IATA)        | : II   |
| Marine pollutant            | : Yes  |

### SECTION 15: Regulatory information

#### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

| <b>Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)</b>  |   |
|--|---|
| EPA TSCA Regulatory Flag   | XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).   |
| <b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro.-omega.-(2-aminomethylethoxy)-, ether with 2-ethyl-2-(hydroxymethyl)-1,3-propanediol (3:1) (39423-51-3)</b> |   |
| EPA TSCA Regulatory Flag   | XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).   |
| <b>Formaldehyde, polymer with benzenamine, hydrogenated (135108-88-2)</b>  |   |
| EPA TSCA Regulatory Flag   | P - P - indicates a commenced PMN substance.<br>XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)). |
| <b>Formaldehyde, oligomeric reaction products with phenol and m-phenylenebis(methylamine) (57214-10-5)</b>   |   |
| EPA TSCA Regulatory Flag   | P - P - indicates a commenced PMN substance.<br>XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)). |
| <b>Phenol, 4-nonyl-, branched (84852-15-3)</b>   |   |
| Subject to reporting requirements of United States SARA Section 313  |   |
| EPA TSCA Regulatory Flag   | SP - SP - indicates a substance that is identified in a proposed Significant New Uses Rule.   |
| SARA Section 313 - Emission Reporting  | 1 %   |



# PRO-SET® LAM-226 Hardener

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| <b>Propylene oxide (75-56-9)</b>  |          |
|---|----------|
| Listed on the United States SARA Section 302<br>Subject to reporting requirements of United States SARA Section 313 |          |
| CERCLA RQ   | 100 lb   |
| SARA Section 302 Threshold Planning Quantity (TPQ)  | 10000 lb |
| SARA Section 313 - Emission Reporting   | 0.1 %    |

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

| <b>Propylene oxide (75-56-9)</b>                      |   |   |   |                                   |
|---|---|---|---|-----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
| Yes   | No  | No  | No  |                                   |

| <b>Isophorone diamine (2855-13-2)</b>                      |
|--|
| U.S. - New Jersey - Right to Know Hazardous Substance List |

| <b>1-Piperazineethanamine (140-31-8)</b>   |
|--|
| U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List |


| <b>1,3-Benzenedimethanamine (1477-55-0)</b>  |
|--|
| U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List |

| <b>Trimethylhexamethylenediamine (25620-58-0)</b>          |
|--|
| U.S. - New Jersey - Right to Know Hazardous Substance List |

| <b>Propylene oxide (75-56-9)</b>  |
|---|
| U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List<br>U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances<br>U.S. - Pennsylvania - RTK (Right to Know) List |

## SECTION 16: Other information

|                           |              |
|---------------------------|--------------|
| <b>Date of issue</b>      | : 04/13/2015 |
| <b>Revision date</b>      | : 01/25/2019 |
| <b>Other information</b>  | : None.      |
| <b>NFPA health hazard</b> | : 3          |
| <b>NFPA fire hazard</b>   | : 1          |
| <b>NFPA reactivity</b>    | : 0          |



|                     |                    |
|---------------------|--------------------|
| HMIS III Rating     |                    |
| <b>Health</b>       | : 3 Serious Hazard |
| <b>Flammability</b> | : 1 Slight Hazard  |
| <b>Physical</b>     | : 0 Minimal Hazard |

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.