



Page 1/12

#### CE Part # 20754-Quart

### Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

#### 1 Identification

- · Product identifier
- · Trade name: SikaBiresin AP014 (A) White
- · Article number: 660963-2
- · Application of the substance / the mixture Polyester filler
- · Details of the supplier of the safety data sheet

Sika Advanced Resins, US

EHS Department

advanced.resins.ehs@us.sika.com

· Manufacturer/Supplier:

Manufacturer:

Sika Advanced Resins

30800 Stephenson Hwy

Madison Heights

MI 48071

USA

- · Information department: Product safety department
- · Emergency telephone number:

During normalopening times: +1 (248) 588-2270 CHEMTREC 24-hour Emergency: +1 (800) 424-9300

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1B
Toxic to Reproduction 2

H350 May cause cancer. Route of exposure: Inhalation.

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



Skin Irritation 2 Eye Irritation 2A H315 Causes skin irritation.

H319 Causes serious eye irritation.

- · Label elements
- $\cdot \textit{GHS label elements} \ \textit{The product is classified and labeled according to the Globally Harmonized System (GHS)}.$

(Contd. on page 2)



Page 2/12

#### Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

(Contd. of page 1)

#### · Hazard pictograms







GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Styrene

#### · Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer. Route of exposure: Inhalation.

Suspected of damaging fertility or the unborn child.

Causes damage to the hearing organs through prolonged or repeated exposure.

#### · Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

*Obtain special instructions before use.* 

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

*Ground/bond container and receiving equipment.* 

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

*Take off contaminated clothing and wash it before reuse.* 

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

*In case of fire: Use CO2, powder or water spray to extinguish.* 

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)



Page 3/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = \*2 Fire = 3Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 100-42-5 Styrene

EINECS: 202-851-5

10-20%

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

US



Sika<sup>®</sup>

Page 4/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

(Contd. of page 3)

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
100-42-5 Styrene	20 ppm
· PAC-2:	
100-42-5 Styrene	130 ppm
· PAC-3:	
100-42-5 Styrene	1100* ppm

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)





Page 5/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

(Contd. of page 4)

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

•	• . 1	1,	1	.11	•	•, •	1	1 1
· Components	with	limit	values	that	rommro	monitoring	at the	workniaco.
Components	WULL	uninu	raines	unu	require	monuomi	ui iii	workpuice.

#### 100-42-5 Styrene

ACGIH TLV | Short-term value: 170 at 40 ppm mg/m³

Long-term value: 85 at 20 ppm mg/m<sup>3</sup>

OSHA PEL Long-term value: 100 ppm mg/m<sup>3</sup>

Ceiling limit value: 200 ppm mg/m<sup>3</sup>

PEL Long-term value: 100 ppm

Ceiling limit value: 200; 600\* ppm

\*5-min peak in any 3 hrs

REL Short-term value: 425 mg/m<sup>3</sup>, 100 ppm

Long-term value: 215 mg/m³, 50 ppm

TLV Short-term value: 20 ppm

Long-term value: 10 ppm

BEI, OTO, A3

#### · Ingredients with biological limit values:

#### 100-42-5 Styrene

BEI 400 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)

40 μg/L Medium: urine Time: end of shift Parameter: Styrene

(Contd. on page 6)





Page 6/12

## Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

(Contd. of page 5)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Pasty
Color: White

Odor: Pungent

Odor threshold: Not determined.

(0 - 1

(Contd. on page 7)





Page 7/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

	(Contd. of page
pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145 °C (293 °F)
· Flash point:	31 °C (87.8 °F)
· Flammability (solid, gaseous):	Flammable.
· Auto igniting:	490 °C (914 °F)
Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
· Explosion limits:	
Lower:	0.9 Vol %
Upper:	6.8 Vol %
Vapor pressure at 20 °C (68 °F):	6 hPa (4.5 mm Hg)
· Density at 20 °C (68 °F):	2.16 g/cm³ (18.03 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.
· Partition coefficient (n-octanol/wate	e <b>r</b> ): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.3 %
Water:	0.0 %
VOC content:	14.76 %
	319.5 g/l / 2.67 lb/gal
Solids content:	56.3 %
Other information	No further relevant information available.

### 10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 8)





Page 8/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

(Contd. of page 7)

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:					
100-42-5	100-42-5 Styrene				
Oral	LD50	>2,000 mg/kg (rat)			
Dermal	LD50	>2,000 mg/kg (rat)			
Inhalative	LC50/4 h	11.8 mg/l (rat)			

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)				
14807-96-6	Talc (Mg3H2(SiO3)4)	3		
100-42-5	Styrene	2A		
13463-67-7	titanium dioxide	2 <i>B</i>		
64-17-5	ethanol	1		
· NTP (Natio	· NTP (National Toxicology Program)			
None of the ingredients is listed.				
· OSHA-Ca (Occupational Safety & Health Administration)				

#### 12 Ecological information

None of the ingredients is listed.

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.

(Contd. on page 9)





Page 9/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

(Contd. of page 8)

- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

#### 14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

UN1866

- · UN proper shipping name
- $\cdot DOT$

Resin solution

· IMDG, IATA

RESIN SOLUTION

- · Transport hazard class(es)
- $\cdot DOT$



· Class

3 Flammable liquids

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids

(Contd. on page 10)



Sika®

Page 10/12

## Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

		(Contd. of page 9
· Label	3	
· Packing group · DOT, IMDG, IATA	III	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Warning: Flammable liquids	
· EMS Number: · Stowage Category	F-E, <u>S-E</u> A	
· Transport in bulk according to Annex		
MARPOL73/78 and the IBC Code	Not applicable.	
· UN ''Model Regulation'':	UN 1866 RESIN SOLUTION, 3, III	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

100-42-5 Styrene

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

· Hazardous Air Pollutants

100-42-5 Styrene

108-10-1 4-methylpentan-2-one

· Proposition 65

· Chemicals known to cause cancer:

100-42-5 Styrene

14808-60-7 Quartz (SiO2)

108-10-1 4-methylpentan-2-one

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 11)



Page 11/12

### Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

,	Contd.	of.	2000	10
١	Comu.	OI	page	10

· Chemicals known to cause reproductive toxicity for males:			
None of the ingredients is listed.			
· Chemicals known to cause developmental toxicity:			
64-17-5	ethanol		
108-10-1	4-methylpentan-2-one		

#### · Carcinogenic categories

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

· Listed in CWC Regulations

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Styrene

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer. Route of exposure: Inhalation.

Suspected of damaging fertility or the unborn child.

Causes damage to the hearing organs through prolonged or repeated exposure.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

(Contd. on page 12)





Page 12/12

#### Safety Data Sheet acc. to OSHA HCS

Printing date 03/21/2023 Reviewed on 03/21/2023

Trade name: SikaBiresin AP014 (A) White

(Contd. of page 11)

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

*In case of fire: Use CO2, powder or water spray to extinguish.* 

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 03/21/2023
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Carcinogenicity 1B: Carcinogenicity - Category 1B

 $Toxic\ to\ Reproduction\ 2:\ Reproductive\ toxicity-Category\ 2$ 

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1

\* \* Data compared to the previous version altered.